


## Product & Installation Details



## General Specifications

| Product Reference                | Construction Material                       | Thermal Management                       | LED Technology                              |
|----------------------------------|---------------------------------------------|------------------------------------------|---------------------------------------------|
| Environment<br>Indoor            | Housing<br>Die Cast Aluminium               | Heat Sink Material<br>Die Cast Aluminium | LED Lifetime @L70/B10<br>> 50000 Hrs.       |
| Installation<br>Ceiling Recessed | Body Finish<br>Powder Coating – White/Black | Cooling Technique<br>Passive Cooling     | Colour Rendering (CRI)<br>CRI80 as Standard |

| General Features                   | Electrical System                      | Controls                                                   | Optical System          |
|------------------------------------|----------------------------------------|------------------------------------------------------------|-------------------------|
| Operating Temperature<br>0°C -50°C | Driven With<br>Constant Current Driver | Standard<br>On / Off                                       | Beam Direction<br>Fixed |
| Ingress Protection (IP)<br>IP20    | Input Voltage<br>220V-240V/50-60Hz     | Optional<br>Mains / Analog / Dali<br>Bluetooth / Phase Cut | Tilt<br>No              |
|                                    | Driver<br>Non-Integrated               |                                                            | Swivel<br>No            |

## Product Details

| Product Name         | Wattage | Dimensions<br>(Sizes in mm) | CCT<br>(Kelvin)    | Lumens  | Beam<br>Angle | Dimming Option               | Finish        |
|----------------------|---------|-----------------------------|--------------------|---------|---------------|------------------------------|---------------|
| CG - 06 -SIGMA I COB | 9W      | 60 Dia X 78 H<br>Ø 55       | 3000 / 4000 / 6500 | 700 lm  | 38 °          | BLE/DALI/ANALOG/PHASE<br>CUT | White / Black |
| CG - 06 -SIGMA I COB | 12W     | 70 Dia X 78 H<br>Ø 65       | 3000 / 4000 / 6500 | 1200 lm | 38 °          | BLE/DALI/ANALOG/PHASE<br>CUT | White / Black |

Manufacturer / Importer

**Core GreenTech LLP**

148/1179, Shree Sai Sahajeevan,  
Motilal Nagar 1, Road No. 3,  
Goregaon – (West) Mumbai – 400104.  
Maharashtra. India

Call: +91 9833297972 | +91 9930526017  
Email: projects@coregreentech.co.in