

Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Indoor	Housing Die Cast Aluminium	Heat Sink Material Die Cast Aluminium	LED Lifetime @L70/B10 > 50000 Hrs.
Installation Ceiling Recessed	Body Finish Powder Coating – White/Black	Cooling Technique Passive Cooling	Colour Rendering (CRI) CRI80 as Standard
General Features	Electrical System	Controls	Optical System
Operating Temperature 0°C - 50°C	Driven With Constant Current Driver	Standard On / Off	Beam Direction Fixed
Ingress Protection (IP) IP20	Input Voltage 220V - 240V/50 - 60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt No
	Driver Non - Integrated		Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 15 - NANO	5W	62 Dia X 25 H Ø 55	3000 / 4000 / 6000	500 lm	120°	BLE/DALI/ANALOG/ PHASE CUT/ TUNABLE	White / Black
CG - 15 - NANO	09W	72 Dia X 28 H Ø 65	3000 / 4000 / 6000	900 lm	120°	BLE/DALI/ANALOG/ PHASE CUT/ TUNABLE	White / Black
CG - 15 - NANO	12W	83 Dia X 31 H Ø 75	3000 / 4000 / 6000	1200 lm	120°	BLE/DALI/ANALOG/ PHASE CUT/ TUNABLE	White / Black
CG - 15 - NANO	15W	105 Dia X 35 H Ø 95	3000 / 4000 / 6000	1500 lm	120°	BLE/DALI/ANALOG/ PHASE CUT/ TUNABLE	White / Black

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India