


Product & Installation Details



General Specifications

Product Reference Environment Indoor Installation Ceiling Recessed	Construction Material Housing Die Cast Aluminium Body Finish Powder Coating – White/Black	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C - 50°C Ingress Protection (IP) IP20	Electrical System Driven With Constant Current Driver Input Voltage 220V - 240V/50 - 60Hz Driver Non - Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt Yes Swivel Yes 30 °

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 16 LAZIO	08W	62 Dia X 75 H Ø 55	3000 / 4000 / 6500	800 lm	24° 38° 55 °	BLE/DALI/ANAL OG/PHASE CUT	Body Color : Matt White Reflector : Black / Chrome
CG - 16 LAZIO	15W	85 Dia X 89 H Ø 75	3000 / 4000 / 6500	1500 lm	24° 38° 55 °	BLE/DALI/ANAL OG/PHASE CUT	Body Color : Matt White Reflector : Black / Chrome
CG - 16 LAZIO	25W	115 Dia X 104 H Ø 95	3000 / 4000 / 6500	2500 lm	24° 38° 55 °	BLE/DALI/ANAL OG/PHASE CUT	Body Color : Matt White Reflector : Black / Chrome

Manufacturer / Importer

Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India