

Product & Installation Details



General Specifications

Product Reference Environment Indoor Installation Ceiling Recessed	Construction Material Housing Die Cast Aluminium Body Finish Powder Coating – White/Black	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C - 50°C Ingress Protection (IP) IP20	Electrical System Driven With Constant Current Driver Input Voltage 220V-240V/50-60Hz Driver Non-Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 18 POLO	7W	75 D X 55 H Ø 60mm	3000 / 4000 / 6500	700 lm	15° 24° 36°	BLE/DALI/ANALOG/P HASE CUT	BODY COLOR : WHITE / BLACK RING COLOR : WHITE / BLACK / CHROME/ROSE GOLD/ GOLD / SHINING BLACK
CG - 18 POLO	12W	85 D X 65 H Ø 75mm	3000 / 4000 / 6500	1200 lm	15° 24° 36°	BLE/DALI/ANALOG/P HASE CUT	BODY COLOR : WHITE / BLACK RING COLOR : WHITE / BLACK / CHROME/ROSE GOLD/ GOLD / SHINING BLACK
CG - 18 POLO	18W	95 D X 75 H Ø 85mm	3000 / 4000 / 6500	1800 lm	15° 24° 36°	BLE/DALI/ANALOG/P HASE CUT	BODY COLOR : WHITE / BLACK RING COLOR : WHITE / BLACK / CHROME/ROSE GOLD/ GOLD / SHINING BLACK

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in