

DEXTER (HONEYCOMB)



Product & Installation Details



General Specifications

Product Reference Environment Indoor Installation Ceiling Recessed	Construction Material Housing Die Cast Aluminium Body Finish Powder Coating – White/Black	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C - 50°C Ingress Protection (IP) IP20	Electrical System Driven With Constant Current Driver Input Voltage 220V - 240V/50 - 60Hz Driver Non - Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 21 DEXTER HONEYCOMB	7- 10W	85 D X 50 H Ø 75mm	3000 / 4000 / 6500	700 lm	15° 24° 36 °	BLE/DALI/ANALOG/ PHASE CUT	BODY COLOR : WHITE / BLACK RING COLOR WHITE / BLACK / CHROME/ROSE GOLD/ SHINING BLACK
CG - 21 DEXTER HONEYCOMB	10- 15W	100 D X 60 H Ø 92mm	3000 / 4000 / 6500	1200 lm	15° 24° 36 °	BLE/DALI/ANALOG/ PHASE CUT	BODY COLOR : WHITE / BLACK RING COLOR WHITE / BLACK / CHROME/ROSE GOLD/ SHINING BLACK
CG - 21 DEXTER HONEYCOMB	15- 20W	125 D X 73 H Ø 115mm	3000 / 4000 / 6500	1800 lm	15° 24° 36 °	BLE/DALI/ANALOG/ PHASE CUT	BODY COLOR : WHITE / BLACK RING COLOR WHITE / BLACK / CHROME/ROSE GOLD/ SHINING BLACK

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in