

PIPE - CYLINDER



Product & Installation Details



General Specifications

Product Reference Environment Indoor Installation Surface	Construction Material Housing Die Cast Aluminium Body Finish Powder Coating – White/Black	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C - 50°C Ingress Protection (IP) IP20 /65	Electrical System Driven With Constant Current Driver Input Voltage 220V - 240V/50 – 60Hz Driver Non - Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG 25 PIPE CYLINDER	5W – 07W	55 D X 75 H	3000 / 4000 / 6500	90 lm/ watt	15° 24 ° 36 ° 55 °	BLE/DALI/ANALOG/ PHASE CUT	BODY COLOR : WHITE / BLACK RING COLOR : WHITE / BLACK / SHINING BLACK/ ROSE GOLD / CHROME / GOLD
CG 25 PIPE CYLINDER	10W – 12W	75 D X 100 H	3000 / 4000 / 6500	90 lm/ watt	15° 24 ° 36 ° 55 °	BLE/DALI/ANALOG/ PHASE CUT	BODY COLOR : WHITE / BLACK RING COLOR : WHITE / BLACK / SHINING BLACK/ ROSE GOLD / CHROME / GOLD

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in