

TURTLE IP65



Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Indoor	Housing Die Cast Aluminium	Heat Sink Material Die Cast Aluminium	LED Lifetime @L70/B10 > 50000 Hrs.
Installation Ceiling Recessed	Body Finish Powder Coating	Cooling Technique Passive Cooling	Colour Rendering (CRI) CRI80 as Standard

General Features	Electrical System	Controls	Optical System
Operating Temperature 0°C - 50°C	Driven With Constant Current Driver	Standard On / Off	Beam Direction Fixed
Ingress Protection (IP) IP65	Input Voltage 220V - 240V/50 - 60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt No
	Driver Non - Integrated		Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 34 TURTLE IP65	07W	61 Dia X 62 H Ø 55	3000 / 4000 / 6500	700 lm	15° 24° 36° 60°	BLE/DALI/ANALOG/PHASE CUT	White / Black / Chrome / Rose Gold / Copper / Gun Metal
CG - 34 TURTLE IP65	12W	81 Dia X 78 H Ø 75	3000 / 4000 / 6500	1200 lm	15° 24° 36° 60°	BLE/DALI/ANALOG/PHASE CUT	White / Black / Chrome / Rose Gold / Copper / Gun Metal
CG - 34 TURTLE IP65	18W	101 Dia X 90 H Ø 95	3000 / 4000 / 6500	1800 lm	15° 24° 36° 60°	BLE/DALI/ANALOG/PHASE CUT	White / Black / Chrome / Rose Gold / Copper / Gun Metal

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in