

AQUA IP65



Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Indoor	Housing Die Cast Aluminium	Heat Sink Material Die Cast Aluminium	LED Lifetime @L70/B10 > 50000 Hrs.
Installation Ceiling Recessed	Body Finish Powder Coating	Cooling Technique Passive Cooling	Colour Rendering (CRI) CRI80 as Standard

General Features	Electrical System	Controls	Optical System
Operating Temperature 0°C - 50°C	Driven With Constant Current Driver	Standard On / Off	Beam Direction Fixed
Ingress Protection (IP) IP65	Input Voltage 220V - 240V/50 - 60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt No
	Driver Non - Integrated		Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 35 AQUA IP65	12W	85 Dia X 70 H Ø 75	3000 / 4000 / 6500	1200 lm	38 °	BLE/DALI/ANALOG/PHAS E CUT	White / Black / Chrome
CG - 35 AQUA IP65	18W	110Dia X 78 H Ø 95	3000 / 4000 / 6500	1800 lm	38 °	BLE/DALI/ANALOG/PHAS E CUT	White / Black / Chrome
CG - 35 AQUA IP65	30W	135 Dia X 91 H Ø 125	3000 / 4000 / 6500	3000 lm	38 °	BLE/DALI/ANALOG/PHAS E CUT	White / Black / Chrome

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India