

KUNG FU – SURFACE CYLINDER



Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Indoor	Housing Die Cast Aluminium	Heat Sink Material Die Cast Aluminium	LED Lifetime @L70/B10 > 50000 Hrs.
Installation Surface mount	Body Finish Powder Coating – White/Black	Cooling Technique Passive Cooling	Colour Rendering (CRI) CRI80 as Standard
General Features	Electrical System	Controls	Optical System
Operating Temperature 0°C - 50°C	Driven With Constant Current Driver	Standard On / Off	Beam Direction Movable
Ingress Protection (IP) IP20	Input Voltage 220V - 240V/50 - 60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt Yes
	Driver Non - Integrated		Swivel No

Product Details

Product Name	Watt	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumen s	Beam Angle	Dimming Option	Finish
CG – 42 KUNG FU (SURFACE CYLINDER)	07W	30 PIPE Dia X 200 PIPE H 75 Dia x 110 H 30 PIPE Dia X 300 PIPE H 75 Dia x 110 H 30 PIPE Dia X 400 PIPE H 75 Dia x 110 H 30 PIPE Dia X 500 PIPE H 75 Dia x 110 H 30 PIPE Dia X 600 PIPE H 75 Dia x 110 H	3000 / 4000 / 6500	700 lm	STRECH ZOOM FROM 24° 58°	BLE/DALI/ANA LOG/PHASE CUT	Body Color : White / Black / Chrome

Manufacturer / Importer

Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in