

NEXA – IP65



Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Outdoor	Housing Die Cast Aluminium	Heat Sink Material Die Cast Aluminium	LED Lifetime @L70/B10 > 50000 Hrs.
Installation Surface mount	Body Finish Aluminium Die cast	Cooling Technique Passive Cooling	Colour Rendering (CRI) CRI80 as Standard

General Features	Electrical System	Controls	Optical System
Operating Temperature 0°C-50°C	Driven With Constant Current Driver	Standard On / Off	Beam Direction Fixed
Ingress Protection (IP) IP65	Input Voltage 220V-240V/50-60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt No
	Driver Non-Integrated		Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - OD – 01 NEXA (ROUND)	07W	70 Dia X 87 H	3000 / 4000 / 6500	700 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey
CG - OD – 01 NEXA (ROUND)	12W	108 Dia X 112 H	3000 / 4000 / 6500	1200 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey
CG - OD – 01 NEXA (SQUARE)	07W	70 x 70 X 87 H	3000 / 4000 / 6500	700 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey
CG - OD – 01 NEXA (SQUARE)	12W	108 X 108 X 112 H	3000 / 4000 / 6500	1200 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in