

SUMO – IP65 DOWN LIGHT



Product & Installation Details



General Specifications

Product Reference Environment Outdoor Installation Surface mount	Construction Material Housing Die Cast Aluminium Body Finish Aluminium Die cast	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C-50°C Ingress Protection (IP) IP65	Electrical System Driven With Constant Current Driver Input Voltage 220V-240V/50-60Hz Driver Non-Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - OD – 02 SUMO	20W	210 Dia X 61 H	3000 / 4000 / 6500	2000 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey
CG - OD – 02 SUMO	30W	310 Dia X 61 H	3000 / 4000 / 6500	3000 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in