

RANGER IP65 SPIKE



Product & Installation Details



General Specifications

Product Reference Environment Outdoor Installation Ground Recessed	Construction Material Housing Die Cast Aluminium Body Finish Stainless Steel	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C-50°C Ingress Protection (IP) IP65	Electrical System Driven With Constant Current Driver Input Voltage 220V-240V/50-60Hz Driver Non-Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - OD – 04 RANGER (WITHOUT HOOD)	12W	85 Dia X 145 X 380 H	3000 / 4000 / 6500	1200 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey
CG - OD – 04 RANGER (WITH HOOD)	12W	85 Dia X 178 X 380 H	3000 / 4000 / 6500	1200 lm	38°	BLE/DALI/ANALOG/PHAS E CUT	Dark Grey

Manufacturer / Importer

Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in