

Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Indoor	Housing Die Cast	Heat Sink Material	LED Lifetime @L70/B10
Installation Ceiling Recessed	Aluminium Body Finish Powder Coating – White/Black	Die Cast Cooling Technique Passive Cooling	> 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features	Electrical System	Controls	Optical System
Operating	Driven With	Standard	Beam
Ingress Protection (IP) IP20	Input Voltage 220V-240V/50-60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt No
	Driver Non-Integrated		Swivel No

Product Details

Product NameWattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming OptionFinish	
CG WS - 06 -RING24W	300 Dia x 35 W 450 Dia x 35 W	3000 / 4000 / 6500	100 lm / watt	110°	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG WS - 06 -RING36W	600 Dia x 35 W 750 Dia x 35 W	3000 / 4000 / 6500	100 lm / watt	110°	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG WS - 06 -RING48W	900 Dia x 35 W 1200 Dia x 35 W	3000 / 4000 / 6500	100 lm / watt	110°	BLE/DALI/ANALOG/PHASE CUT	White / Black

Manufacturer / Importer
Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai –
400104.
Maharashtra, India
Call: +91 9833297972 | +91
9930526017
Email: projects@coregreentech.co.in