


Product & Installation Details



General Specifications

Product Reference	Construction Material	Thermal Management	LED Technology
Environment Indoor	Housing Die Cast Aluminium	Heat Sink Material Die Cast Aluminium	LED Lifetime @L70/B10 > 50000 Hrs.
Installation Ceiling Recessed	Body Finish Powder Coating – White/Black	Cooling Technique Passive Cooling	Colour Rendering (CRI) CRI80 as Standard
General Features	Electrical System	Controls	Optical System
Operating Temperature 0°C - 50°C	Driven With Constant Current Driver	Standard On / Off	Beam Direction Fixed
Ingress Protection (IP) IP20	Input Voltage 220V-240V/50-60Hz	Optional Mains / Analog / Dali Bluetooth / Phase Cut	Tilt No
	Driver Non-Integrated		Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - DL – 02 CRUZE	12W	103 Dia X 40 H Ø 95	3000 / 4000 / 6500	1200 lm	38 °	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG - DL – 02 CRUZE	18W	153 Dia X 40 H Ø 145	3000 / 4000 / 6500	1800 lm	38 °	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG - DL – 02 CRUZE	24W	211 Dia X 40 H Ø 203	3000 / 4000 / 6500	2400 lm	38 °	BLE/DALI/ANALOG/PHASE CUT	White / Black

Manufacturer / Importer

Core GreenTech LLP

148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in