

Product & Installation Details



General Specifications

Product Reference Environment Indoor Installation Ceiling Recessed	Construction Material Housing Die Cast Aluminium Body Finish Powder Coating – White/Black	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C - 50°C Ingress Protection (IP) IP20	Electrical System Driven With Constant Current Driver Input Voltage 220V-240V/50-60Hz Driver Non-Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG 07 MASH MOVABLE	8W	74 D X 55 H Ø 64	3000 / 4000 / 6500	600 lm	24° 38° 55°	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG 07 MASH MOVABLE	12W	81 D X 54 H Ø 70	3000 / 4000 / 6500	1000 lm	24° 38° 55°	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG 07 MASH MOVABLE	15W	89 D X 55 H Ø 79	3000 / 4000 / 6500	1300 lm	24° 38° 55°	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG 07 MASH MOVABLE	20W	114 D X 79 H Ø 104	3000 / 4000 / 6500	1800 lm	24° 38° 55°	BLE/DALI/ANALOG/PHASE CUT	White / Black
CG 07 MASH MOVABLE	20W	137 D X 79 H Ø 125	3000 / 4000 / 6500	2800 lm	24° 38° 55°	BLE/DALI/ANALOG/PHASE CUT	White / Black

Manufacturer / Importer

Core GreenTech LLP
148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in