

Product & Installation Details



General Specifications

Product Reference Environment Indoor Installation Ceiling Recessed	Construction Material Housing Die Cast Aluminium Body Finish Powder Coating – White/Black	Thermal Management Heat Sink Material Die Cast Aluminium Cooling Technique Passive Cooling	LED Technology LED Lifetime @L70/B10 > 50000 Hrs. Colour Rendering (CRI) CRI80 as Standard
General Features Operating Temperature 0°C - 50°C Ingress Protection (IP) IP20	Electrical System Driven With Constant Current Driver Input Voltage 220V-240V/50-60Hz Driver Non-Integrated	Controls Standard On / Off Optional Mains / Analog / Dali Bluetooth / Phase Cut	Optical System Beam Direction Fixed Tilt No Swivel No

Product Details

Product Name	Wattage	Dimensions (Sizes in mm)	CCT (Kelvin)	Lumens	Beam Angle	Dimming Option	Finish
CG - 14 STELLER	7W	39 Dia X 59 H Ø 33	3000 / 4000 / 6500	700 lm	38 °	BLE/DALI/ANALOG/P HASE CUT	Matt White /Gun Metal Black/ Shinning Copper
CG - 14 STELLER	12W	58 Dia X 70 H Ø 52	3000 / 4000 / 6500	1200 lm	38 °	BLE/DALI/ANALOG/P HASE CUT	Matt White /Gun Metal Black/ Shinning Copper
CG - 14 STELLER	18W	75 Dia X 85 H Ø 65	3000 / 4000 / 6500	1800 lm	38 °	BLE/DALI/ANALOG/P HASE CUT	Matt White /Gun Metal Black/ Shinning Copper

Manufacturer / Importer

Core GreenTech LLP

148/1179, Shree Sai Sahajeevan,
Motilal Nagar 1, Road No. 3,
Goregaon – (West) Mumbai – 400104.
Maharashtra. India

Call: +91 9833297972 | +91 9930526017
Email: projects@coregreentech.co.in