

Ceiling Downlight Flato

700 mm Dia



APPLICATION AREAS

Office buildings, Retail,
Supermarkets, Hospitality,
Library



LOW Glare



PF >0.95



CRI



Burning Hours



Green Energy

TECHNICAL SPECIFICATIONS

PRODUCT CODE	Ceiling Downlight Flato	CRI (Ra)	85+
ENVIRONMENT	-	LED LIFE	45,000 HRS
DIMENSION (MM)	10W - 86mm x (H)33mm Cut-out:75mm 15W - 115mm x (H)42mm Cut-out:105mm 20W - 142mm x (H)50mm Cut-out:130mm	UGR	<17
CUT OUT SIZE (MM)	-	INPUT VOLTAGE	110 To 270 V
HOUSING	DIE - CAST ALUMINIUM	INPUT POWER	-
LENS / DIFFUSER	-	POWER FACTOR	>0.95
BEAM ANGLE	-	THD	<10%
HEAT SINK MATERIAL	ALUMINIUM	CONTROL GEAR	Remote
COOLING TECHNIQUE	PASSIVE	MOUNTING	
LED FITTED	CREE/ BRIDGELUX	DRIVER PROTECTION	OVP, Short Circuit, SURGE
LED FLUX	-	DIMMING/EMERGENCY	Optional
DELIVERED LUMENS	100LM/WATT	KIT/SENSOR	
CCT (K)	3000K / 4000K / 6500K	IP RATING	20
		PACKING QTY	-
		GROSS WEIGHT	-
		CARTOON SIZE	-