

Ceiling Downlight Pin Spot

700 mm Dia



APPLICATION AREAS

Office buildings, Retail,
Supermarkets, Hospitality,
Library



LOW Glare



PF >0.95



CRI



Burning Hours



Green Energy

TECHNICAL SPECIFICATIONS

PRODUCT CODE	Ceiling Downlight Pin Spot
ENVIRONMENT	-
DIMENSION (MM)	5W - 40D X 58H 35mm 10W - 65D X 59H 55mm 15W - 74D X 72H 65mm
CUT OUT SIZE (MM)	-
HOUSING	DIE - CAST ALUMINIUM
LENS / DIFFUSER	-
BEAM ANGLE	-
HEAT SINK MATERIAL	ALUMINIUM
COOLING TECHNIQUE	PASSIVE
LED FITTED	CREE/ BRIDGELUX
LED FLUX	-
DELIVERED LUMENS	100LM/WATT
CCT (K)	3000K / 4000K / 6500K

CRI (Ra)	85+
LED LIFE	45,000 HRS
UGR	<17
INPUT VOLTAGE	110 To 270 V
INPUT POWER	-
POWER FACTOR	>0.95
THD	<10%
CONTROL GEAR	Remote
MOUNTING	
DRIVER PROTECTION	OVP, Short Circuit, SURGE
DIMMING/EMERGENCY	Optional
KIT/SENSOR	
IP RATING	20
PACKING QTY	-
GROSS WEIGHT	-
CARTOON SIZE	-