

Bover Pendant

The Bover Pendant combines decoration with sound management through acoustically rated panels, offering both aesthetics and functionality for your space.



APPLICATION AREAS

Office buildings, Retail,
Supermarkets, Hospitality,
Library

TECHNICAL SPECIFICATIONS

PRODUCT CODE	Acoustic Lights Lux Pendant
DIMENSION (MM)	400mm D x 285mm H 525mm D x 375mm H 650mm D x 475mm H
HOUSING	PET ACOUSTIC
LENS / DIFFUSER	HIGH TRANSMISSION PMMA
COOLING TECHNIQUE	PASSIVE
LED FITTED	CREE/ BRIDGELUX
DELIVERED LUMENS	100LM/WATT
CCT (K)	3000K / 4000K / 6500K
IP RATING	20
BEAM ANGLE	110 Degree

CRI (Ra)	80+
LED LIFE	50,000 Burning Hours
UGR	<17
INPUT VOLTAGE	118 To 270 V
POWER FACTOR	0.97
THD	<18%
CONTROL GEAR	Remote
MOUNTING	
DRIVER PROTECTION	OVP, Short Circuit, SURGE
DIMMING/EMERGENCY KIT/SENSOR	Optional

Manufacturer / Importer

Core GreenTech LLP

www.coregreentech.co.in

© Copyright 2024 Core GreenTech LLP. All rights reserved

We specialize in crafting
custom solutions tailored to the
specific needs of each client's site.

Call: +91 9833297972 | +91 9930526017

Email: projects@coregreentech.co.in